The Associated General Contractors of America

Comments on Effluent Limitations Guidelines and Standards for the Construction and Development Point Source Category; Docket ID No. EPA–HQ–OW–2010–0884

SUBMITTED DATE:
March 5, 2012

SUBMITTED TO:
Water Docket
U.S. Environmental Protection Agency
Mail Code 28221T
1200 Pennsylvania Avenue, NW
Washington, DC 20460
ATTN: Docket ID No. EPA–HQ–OW–2010–0884

SUBMITTED VIA:
Regulations.gov: http://www.regulations.gov

SUBMITTED BY:

Leah F. Pilconis
Consultant on Environmental Law & Policy
Senior Environmental Advisor to AGC of America
Direct: 703-837-5332
Fax: 703-837-5401
E-mail: pilconisl@agc.org

On behalf of the Associated General Contractors of America
2300 Wilson Boulevard, Suite 400
Arlington, VA 22201

A. Holding final permittees to a tougher sampling and analyses standards than the "data suppliers" that helped to "establish" the limit creates an unjust and arbitrary regulatory process and outcome that EPA must prevent.

X. EPA can more appropriately satisfy its ELG rulemaking obligations through a non-numeric, BMP-based technology standard.

XI. Data Quality Considerations

XII. Analysis of Passive Treatment Data from Studies by Dr. McLaughlin

XIII. Comments on Semi-Passive Control Technologies

A. Water Treatment Assessment Report, Petersburg, Alaska Airport (Docket ID: EPA-HQ-OW-2010-0884-0007, or DCN 70000, also two auxiliary magazine articles, DCN 70001 and 70002, or EPA-HQ-OW-2010-0884-0008 and -0009)

B. StormKlear Control Technologies and Sites

XIV. AGC's Response to Additional Questions Presented in EPA's Notice

A. Stormwater Collection Procedures and Measuring Equipment

B. Conditions where an Exemption from a Numeric Turbidity Limit is Needed, including Rain Intensity as well as a Design Depth Rain Event

C. Cold Weather Conditions Affecting Treatment

D. Toxicity of Polymers

XV. Conclusion

AGC Comments

AGC Comments
EPA ELG Data Notice -

B. Turbidity is not a good indicator of soil loss from a construction site.

As discussed above, turbidity measures the opacity of water, representing both dissolved and suspended solids in the water column. Thus, turbidity monitoring does not accurately measure the mass/volume of soil being lost from a site, but instead reflects the aesthetic nature of the runoff (clear, cloudy, etc.). For example, soils with a heavy clay content (easily dissolved) will have a higher turbidity measurement for a relatively small quantity of soil in the water, while a sandy loam will have a lower turbidity measurement for a larger quantity of soil in the water, because the larger particles will not stay suspended and they won't dissolve. Thus, a turbidity measurement is not a good standardized indicator of the prevention of soil loss from a construction site.

EPA should limit its data collection to analytical measurements of TSS from outfalls at construction sites. AGC maintains that EPA must use a mass-based analysis (TSS) to represent the quantity of soil lost from a construction site, rather than a turbidity reading, that only provides information on a secondary standard for water quality and/or aesthetics.

C. EPA's C&D ELG focus has always been on conventional pollutants and it must conform to CWA control strategies for conventional pollutants.

Whatever pollutant that EPA targets for regulation will dictate the technology standards analysis and statutory authority governing EPA's ELG standards setting efforts. To promulgate an ELG, EPA identifies the pollutants to be regulated in a particular industry, as well as a technology that represents the statutorily prescribed level of control *for those pollutants*. The CWA articulates several levels of control for pollutants (*e.g.*, "best practicable control technology currently available," "best available technology economically achievable," and "best conventional pollutant control technology").[1]

For example, by July 1, 1977, EPA was to establish effluent limitations based on the "best practicable control technology currently available" (BPT) for existing sources discharging pollutants (sources other than publicly-owned treatment works).[2] Then, by March 31, 1989, newer technology standards were to govern depending on whether the pollutant of concern was conventional, toxic, or non-conventional. By March 31, 1989, existing sources of conventional pollutants[3] were to be subject to effluent limitations applying "the best conventional pollutant control technology" (BCT).[4] Similarly, effluent limitations from existing sources for both toxic and non-conventional pollutants also were mandated by March 31, 1989 based on the "best available technology economically achievable" (BAT) technology standard.[5]

[1] *See* 33 U.S.C. §§ 1314(b)(1)(A), (b)(2)(A), (b)(4)(A).

[2] I*d.* § 1311(b)(1)(A).

[3] "Conventional pollutants" include biological oxygen demand, suspended solids (such as sediment), fecal coliform, and pH. 33 U.S.C. § 1314(a)(4).

[4] 33 U.S.C. § 1311(b)(2)(E) references § 1314(b)(4), which pertains to conventional pollutants.

[5] 33 U.S.C. § 1311(b)(2)(A) (setting forth the BAT standard), references subsections (C) and (D) which pertain to certain toxic pollutants. Subsection (b)(2)(A) also references subsection (F), establishing BAT for "all" remaining pollutants not covered elsewhere in subparagraph (2) (*i.e.,* non-conventional pollutants).

In the 2009 C&D ELG rulemaking, EPA applied a BAT standard to turbidity, arguing that because turbidity is not specifically listed as a "conventional" pollutant, it must be a "non-conventional" pollutant subject to BAT. That argument is unjustified. EPA's focus has been on discharging sediments from construction sites. Sediments are conventional pollutants. EPA can characterize "sediment" through turbidity monitoring or use any term it chooses, but in the end, EPA is still regulating sediment discharges. Hence, a BCT analysis is the only reasonably and appropriate CWA analysis that should be applied.

Hence, EPA should simplify its approach and target TSS as its pollutant and recognize that any method of measuring suspended sediments necessitates, from a CWA perspective, an appropriate BCT analysis. In the CBIA case referenced above, the California Superior Court looked at turbidity as merely an alternate method for measuring TSS, thereby equating turbidity to "conventional" pollutant discharges subject to BCT. Ultimately, the court found that the State had not properly met the prerequisites of the BCT standard in setting a numeric turbidity limit in the California General Permit. Other states, including Minnesota and Washington to name a few, also equate turbidity to "conventional" pollution subject to BCT.

In conducting an appropriate BCT analysis, CWA Section 304(b) requires EPA consider certain factors and also employ a "cost reasonableness" evaluation comparing the removal efficiencies of various technologies to publicly-owned treatment works. Factors EPA should consider include: "the age of equipment and facilities involved, the process employed, the engineering aspects of the application of various types of control techniques, process changes, non-water quality environmental impact (including energy requirements), and such other factors as the Administrator deems appropriate; . . ." 33 U.S.C. § 1314(b)(4)(B). Information relating to these must also be collected by EPA for it to properly develop any future ELG standard.

The D.C. Circuit has clearly stated: "A statutorily mandated factor, by definition, is an important aspect of any issue before an administrative agency . . . ." *Public Citizen v. Federal Motor Carrier Safety Admin.*, 374 F.3d 1209, 1216 (D.C. Cir. 2004). If EPA cannot assess the factors associated with the data it collects, it is vulnerable to claims that it acted arbitrarily and capriciously and abused its discretion by failing to consider several CWA § 304(b) factors. *See Texas Oil and Gas Ass'n v. EPA*, 161 F.3d 923, 934 (5th Cir. 1998) (EPA's "[f]ailure to consider [any] factor is therefore, under the plain meaning of the Act and its implementing regulations, an abuse of discretion."). This issue raises particular concerns in light of the significant data collection challenges and inadequacies in data already in EPA's docket.

Obviously, if EPA could defend using turbidity to avoid a BCT analysis, it still must assess and analyze similar factors under the CWA for establishing BAT ELG standards. Under either a BCT or BAT rulemaking process, EPA cannot avoid the critical issues associated with collecting reliable data that address the factors set forth in appropriate sections of CWA 304(b).

D. EPA must not collect and combine performance data on multiple pollutant parameters for purposes of setting a NEL for only one of those parameters.

EPA currently seeks information on the "costs, effectiveness, and feasibility of different technologies to control [total suspended solids] TSS, settleable solids, suspended sediment concentration, and

turbidity…." 77 *Fed. Reg.* at 118. EPA's rather random approach to collecting data for controlling different parameters to set a limit for "turbidity" will cause confusion and lacks reliability. (EPA is clearly focused upon setting a numeric limit for turbidity. *Id.* at 120.) Even though one could argue that these different parameters are interrelated in that they represent different ways of measuring soil particles in water, they are not interchangeable. The soil type, test method, and other factors prevent EPA from making any national assumptions that results relating to one parameter truly reflect comparable results for tests on another parameter.

V. Even EPA's own cost-benefit analysis shows limited environmental benefits associated with its numeric turbidity limit, but extremely high compliance costs.

Stormwater discharges associated with construction activity already are heavily regulated and largely controlled for sediment, a conventional pollutant. When considering the overall contribution of sediment from construction sites relative to other sources there is limited benefit achieved.

In 2004 EPA recognized the efficacy of the existing federal, state, and local effort when it stated that "construction site stormwater discharges are already being adequately addressed through the existing program."[6]

improved, it should have initiated that effort prior

AGC Comments

Finally, EPA requests comment on the factors it should consider in evaluating treatment performance data. Other than the descriptive information listed above, AGC believes that EPA must consider the following when evaluating performance data for purposes of establishing a numeric effluent limitation:

AGC

meet the new more stringent standard of quality from the Safe Drinking Water Act of 1996 (SDWA),[13]

On August 5, 2011, EPA released a draft *Scientific Integrity Policy*. *See* http://www.epa.gov/stpc/pdfs/draft-scientific-integrity-policy-aug2011.pdf (Draft Science Policy). In it, EPA reiterates that "science is the backbone of EPA's decision-making." Moreover, EPA recognizes that the "environmental policies, decisions, guidance and regulations that impact the lives of all Americans every day are grounded, at a most fundamental level, in sound, high quality science." Draft Science Policy at 1.

EPA's data collection January 3 Notice should be analyzed and assessed in light of the President's commitment to scientific integrity. In that light, the notice raises more questions about how EPA will collect and analyze data to ensure future decisions about any numeric effluent limit for turbidity will be grounded in such high quality science.

XII. Analysis of Passive Treatment Data from Studies by Dr. McLaughlin

Dr. McLaughlin's studies were used by EPA to support its December 2009 turbidity limit of 280 NTU. There were three "passive treatment" sites and very few rain events (one site only had three events) represented in the data accepted by EPA. *See* NCR.1, NCR.2 and NC-Road in "Target Turbidity Limits for Passive Treatment Systems" (Docket ID EPA-HQ-OW-2008-0465-0984.6). Dr. McLaughlin has supplied additional data from three new studies at two (or possibly three) locations: "Attachment 1" which had three sampling events, "Basin 3 Out" which had four sampling events, and "Basin 4 Out" which had three sampling events. *See*

AGC Comments

dataset and diminish or eliminate the dataset's value for regulatory purposes. Our concern is that the samplers may be more prone to malfunction during the larger or more intense rain events. Hence, the turbidity results of the sampled events are skewed towards lower flow events that are more easily treated by passive treatment and reflect lower (not representative) turbidity values.

- **The McLaughlin studies were performed as comparisons of their PTS setups to conventional BMPs, and were not intended to be used to set regulatory numeric limits.** McLaughlin's methods and procedures for collecting samples and their subsequent analyses and screening may be suitable for an academic research project to evaluate PTS effectiveness relative to other types of BMPs, but they are not appropriate for setting an NEL. For example, McLaughlin's NC-Road site (note this was a three acre Limited Impact Development (LID) site for three buildings) report indicates that the installation of LID devices may conflict with stormwater BMPs needed during the construction phase: "This is an LID development involving three buildings, and due to the small construction site footprint much of the site is under constant disturbance by the various contractors involved. This creates challenges to maintaining the PTS and keeping stormwater flowing through stabilized ditches with the treatment system." The McLaughlin report suggests a solution would be to temporarily install the PTS, including a sediment basin, out of the construction envelope and route all stormwater to it. Once the site is stabilized, these areas could be reclaimed or used for post-construction stormwater treatment. Most sites would not have an option to install the PTS and sediment basins temporarily offsite, as McLaughlin suggests.
- **At least one McLaughlin site was poorly managed due to travel distance.** EPA also included in its January 3 Notice a brief discussion of data from an older McLaughlin paper titled "Water Quality Improvements Using Modified Sediment Control Systems on Construction Sites" (DCN 70063, or Docket ID EPA-HQ-OW-2010-0884-0062). In that paper, McLaughlin noted that the site was more than three hours away; therefore, his team could not get to the site as needed and their sampling system was frequently disrupted by activities at the site.

XIII. Comments on Semi-Passive Control Technologies

EPA is asking for public input on how it is characterizing PTS and ''semi-passive'' treatment systems in the context of construction site stormwater management. According to EPA, PTS are "practices that do not rely on computerized systems with pumps, filters and real-time controls but do incorporate a treatment chemical to aid in sediment and turbidity removal." But "when pumps are utilized to pump the water through a manifold or other apparatus to dose the chemical, this type of treatment has been characterized by the industry as semi-passive treatment." 77 *Fed. Reg.* 112.

Overall, AGC members have expressed concern about any treatment technology that requires the stormwater to first be stored in ponds, tanks or other impoundments in order to provide a controlled release. These storage requirements add significant costs and additional operational considerations to address, particularly during extended periods of precipitation. Also

AGC

meters are also susceptible to equipment malfunctions e4scnee000should be developed. 665DCw 12 Td (E

has more than one inch of rainfall, there would be a 24-hour exemption from meeting the numeric limit, starting from the beginning of this rain event. The event could be verified either directly at the site, or by information from the closest official weather station. High intensity rain events cause the most impact to stormwater BMPs and the discharge at a site. Such rain events can cause much larger amounts of sediment to be transported in the runoff, and the sudden high flow can cause irregular PAM dosing from passive treatment BMPs, or even bypass the PTS altogether. Even if a site has room and has installed large detention and settling ponds to collect this runoff, the higher sediment release along with a less certain polymer dosage might mean that even these ponds provide insufficient settling time.

- **Miscellaneous** – Because we still do not fully understand all of the issues associated with monitoring for any future numeric limit, there are bound to be issues that have not previously been addressed by EPA or included in these comments. AGC encourages EPA to use the comments to its January 3 Notice to further refine its ELG approach and then to request more comments after it can more precisely articulate its strategy and approach to collecting data and possibly setting a numeric limit. AGC does not endorse or support a numeric limit but has provided comments throughout this submission in good faith to help EPA consider all of the issues associated with possibly setting a limit. In doing so, AGC admits that there are many circumstances that it and EPA have not considered and any attempt to interpret these comments as the full extent of all issues associated with a numeric limit for the C&D ELG rulemaking is misguided.

C. Cold Weather Conditions Affecting Treatment

It is important that EPA recognize the challenges to employing treatment technologies on construction sites during certain cold weather conditions, namely: 1) during the thaw period when large amounts of snow still remain on the site, altering site runoff (or run-on) patterns, and drastically increasing runoff during rain events due to accelerated snow melt, or 2) periods of alternating freezes and thaws, where passive polymer application BMPs can become coated with ice, frozen, or covered in snow and rendered ineffective. While it appears that the adve0032 Tc 3.7wc not end50tMilanumc-26.08 0 Tt aTA878>TjEMCsy 9/5.tn

EPA's 2009 Final C&D ELG docket and response to comments appeared to disregard toxicity concerns. That was wrong and EPA must account for the costs and impacts associated with using chemicals in passive and semi-passive treatment, assuming those become model technologies. These costs include administrative costs related to obtaining state (or EPA) approval to use chemicals, the potential costs of collecting and treating stormwater to remove excess or residual chemical concentrations, and the potential for impacts on aquatic species associated with those chemicals. AGC does not support or endorse EPA's reliance on chemical usage or possible mandate of chemicals in passive or semi-passive technologies when setting any nationally applicable ELG standard. They may be appropriate in certain circumstances, but cannot be supported as a national standard. If they are relied upon for such, the true costs associated with their use must be included in the cost analysis and potential harms offset against benefits.

XV. Conclusion

AGC appreciates the opportunity to provide comments and voice significant concerns with EPA's data collection strategy and issues raised in the January 3, 2012, *Federal Register* Notice. We encourage EPA to work closely with the construction industry during the comment review process.